# 850 VA "Basic 850" UPS, Shuko output sockets, black

EG-UPS-B850

## ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use





## Features

- Uninterruptable 850 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- LED status indication
- Short circuit protection
- Surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

## Specifications

UPS type: line interactive
Input: AC 220V±25%, 50Hz/60Hz ±10%
Output: AC 220V±10%, 50Hz/60Hz ±0.5% (on battery)
Switching time: 4-8ms
Backup time: up to.20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12V/8Ah x 1 pc

Charge time: up to 12 hours
Sockets: 2 x Schuko output (CEE 7/4)
Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing
Power: 850 VA (510 W)

## Packaging

| | |
|---|---|
| Q'ty in crtn, pcs | 4 |
| Crtn volume, CUM | 0.045356 |
| Crtn weight, kgs | 21.4 |
| Individual package size LxWxH: | 338x147x210 mm |
| Carton size LxWxH: | 580x340x230 mm |
| Country of origin | CN |
| Barcode | 8716309087070 |
| Customs code | 8504408490 |

## System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

## Package contents

UPS
User manual

## Certificates

Copyright © 2009–2020, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com